

Anti-static HPL

High pressure laminate according to EN 438.

PIXEL Raised Access Flooring offers comprehensive solutions of High Tech Raised Access Flooring Systems for the construction industry. PIXEL Raised Access Flooring are manufactured according to most common international standards to meet the requirements of commercial, residential, governmental, transportation, healthcare, and educational projects. In addition to its wide array of Raised Flooring panels and variety of finishes, PIXEL provides the technical expertise via its qualified and dedicated team of engineers and industry-experts in the field. PIXEL range of products is manufactured from high quality raw material and designed to meet all International Standards.

Performance:

- High resistance to wear and tear
- High resistance to scratching
- High resistance to impact
- Resistance to high temperatures
- Special anti-static properties
- Easy cleaning and maintenance.



Anti-static HPL

High pressure laminate according to EN 438.

| Property | Test Method (EN 438:2005) | Unit | Values |
|------------------------|---------------------------|--------------------|---|
| Thickness | EN438-2.5 | mm | 0.9; 1,2; 2 |
| Density | ISO 1183 | gr/cm ³ | > 1,35 |
| Impact Resistance | EN 438-2.20 | N | > 20 |
| Stain Resistance | EN 438-2.26 | Rating | > 4 |
| Resistance to wet heat | EN 12721 | Rating | > 4 |
| Resistance to abrasion | EN 13329 - Annex E | Revs | AC 2 IP > 1500 |
| Electrical Resistance | DIN 51953 / EN 1081 | Ω | Anti-static 1.0x10 ⁶ ~ 1.0x10 ⁹ |