



PIXEL Under-Structure System PEDESTALS

PIXEL Raised Access Flooring offers comprehensive solutions of High Tech Raised Access Flooring Systems for the construction industry. PIXEL Raised Access Flooring are manufactured according to most common international standards to meet the requirements of commercial, residential, governmental, transportation, healthcare, and educational projects. In addition to its wide array of Raised Flooring panels and variety of finishes, PIXEL provides the technical expertise via its qualified and dedicated team of engineers and industry-experts in the field. PIXEL range of products is manufactured from high quality raw material and designed to meet all International Standards.

Type 1: PIXPD-F

Height: 75-500 mm

Pedestal Head:

Electro galvanized circular steel of 98mm diameter x 2.3mm thickness welded at the center to M18 threaded steel with 2 leveling and locking nuts.

Pedestal Base:

Electro galvanized steel Plate.
Dimensions: 100x100mm with 2.3mm thickness, welded at the center to 21mm diameter tube.
Thickness is 1.2mm.

Code	Pedestal Height (mm)	Adjustment Rang (mm)
PPF-1	75	75 - 100
PPF-2	100	100 - 125
PPF-3	150	125 - 175
PPF-4	200	175 - 225
PPF-5	250	225 - 275
PPF-6	300	275 - 325
PPF-7	350	325 - 375
PPF-8	400	375 - 425
PPF-9	450	425 - 475
PPF-10	500	475 - 525

Type 2: PIXPD-S

Height: 510-1200 mm

Pedestal Head:

Electro galvanized circular steel
Dimensions: 98mm diameter x 2.3mm thickness welded at the center to M18 threaded steel with 2 leveling and locking nuts.

Pedestal Base:

Electro galvanized steel Plate,
Sizes: 100x100mm x 2.3mm thickness, welded at the center to 25mm diameter tube.
Thickness: 1.2mm.

Code	Pedestal Height (mm)	Adjustment Rang (mm)
PPS-1	550	525 - 575
PPS-2	600	575 - 625
PPS-3	650	625 - 675
PPS-4	700	675 - 725
PPS-5	750	725 - 775
PPS-6	800	775 - 825
PPS-7	850	825 - 875
PPS-8	900	875 - 925
PPS-9	950	925 - 975
PPS-10	1000	975 - 1025
PPS-11	1050	1025 - 1075
PPS-12	1100	1075 - 1125
PPS-13	1150	1125 - 1175
PPS-14	1200	1175 - 1225

PIXEL Under-Structure System PEDESTALS

Type 3: PIXPD-T

Height: 1210-2000 mm

Pedestal Head:

Electro galvanized circular steel of 98mm diameter x 2.3mm thickness welded at the center to M18 threaded steel with 2 leveling and locking nuts.

Pedestal Base:

Electro galvanized steel Plate.
Sizes: 100x100mm x 2.3mm thickness, welded at the center to 32mm diameter tube,
Thickness: 1.2mm.

Axial Load: > 20 Kn.

Fire Performance: Class A.

Code	Pedestal Height (mm)	Adjustment Rang (mm)
PPT-1	1200	1175 - 1225
PPT-2	1250	1225 - 1275
PPT-3	1300	1275 - 1325
PPT-4	1350	1325 - 1375
PPT-5	1400	1375 - 1425
PPT-6	1450	1425 - 1475
PPT-7	1500	1475 - 1525
PPT-8	1550	1525 - 1575
PPT-9	1600	1575 - 1625
PPT-10	1650	1625 - 1675
PPT-11	1700	1675 - 1725
PPT-12	1750	1725 - 1775
PPT-13	1800	1775 - 1825
PPT-14	1850	1825 - 1875
PPT-15	1900	1875 - 1925
PPT-16	1950	1925 - 1975
PPT-17	2000	1975 - 2025

